

AIR HOSE 15 BAR STANDARD DUTY



- TUBE** : Natural-synthetic rubber Blend
- REINFORCEMENT** : High tensile textile yarn
- COVER** : Black synthetic elastomer - abrasion and ozone resistant SBR
- TEMP RANGE** : -25° C +80° C (-13° F +176° F)
- APPLICATIONS** : Compressed air and general industrial applications
- PROPERTIES** : Flexible
High abrasion
Uniform thickness
- STANDARD COLOUR AND FINISH** : Inner tube - Black
Outer cover - Black
Finish - Smooth/Wrapped
- APPLICABLE STD** : ISO 2398 ; IS 446

PART NO.	INTERNAL DIAMETER		OUTER DIAMETER	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS		WEIGHT	STD. LENGTH
	Inch	mm	mm	bar	psi	bar	psi	Inch	mm	Kg/m	Mtr
EHA1129-06	1/4	6	13	15	215	45	650	1.9	48	0.165	100/50
EHA1129-08	5/16	8	15	15	215	45	650	2.5	64	0.215	100/50
EHA1129-10	3/8	10	17	15	215	45	650	3.1	80	0.250	100/50
EHA1129-12	1/2	12.5	21	15	215	45	650	4.1	104	0.340	100/50
EHA1129-16	5/8	16	24	15	215	45	650	5.0	128	0.430	100/50
EHA1129-19	3/4	19	27	15	215	45	650	6.0	152	0.520	100/50
EHA1129-25	1	25	35	15	215	45	650	7.9	200	0.740	100/50

Note : Taco shell packing available in 25, 50 and 100 feet with (1/4 NPT) and without fittings