

AIR HOSE 20 BAR HEAVY DUTY



- TUBE** : Natural-synthetic rubber Blend
- REINFORCEMENT** : High tensile textile yarn
- COVER** : synthetic elastomer - abrasion and ozone resistant SBR
- TEMP RANGE** : -25° C +80° C (-13° F +176° F)
- APPLICATIONS** : Compressed air and general industrial applications
- PROPERTIES** : Flexible
High abrasion
Uniform thickness
- STANDARD COLOUR AND FINISH** : Inner tube - Black
Outer cover - Black / Blue
Finish - Smooth/Wrapped
- APPLICABLE STD** : ISO 2398 ; IS 446

PART NO.	INTERNAL DIAMETER		OUTER DIAMETER mm	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS		WEIGHT Kg/m	STD. LENGTH Mtr
	Inch	mm		bar	psi	bar	psi	Inch	mm		
EHA1130-06	1/4	6	13	20	300	60	900	2.3	58	0.170	100/50
EHA1130-08	5/16	8	15	20	300	60	900	2.9	74	0.220	100/50
EHA1130-10	3/8	10	17	20	300	60	900	3.5	90	0.260	100/50
EHA1130-12	1/2	12.5	21	20	300	60	900	4.5	114	0.350	100/50
EHA1130-16	5/8	16	24	20	225	60	650	5.4	138	0.440	100/50
EHA1130-19	3/4	19	27	20	300	60	900	6.4	162	0.530	100/50
EHA1130-25	1	25	35	20	300	60	900	8.3	210	0.750	100/50

Note : Taco shell packing available in 25, 50 and 100 feet with (1/4 NPT) and without fittings