

AIR - WATER HOSE



TUBE	: Natural-synthetic rubber Blend
REINFORCEMENT	: One or multiple layers of Textile reinforced subjected to ID (1.1/4", 1.1/2" and 2" double braid)
COVER	: Synthetic elastomer - abrasion and ozone resistant
TEMP RANGE	: -25° C +80° C (-13° F +176° F)
APPLICATIONS	: Compressed air and general industrial applications
PROPERTIES	: Uniform Thickness Flexible
STANDARD COLOUR AND FINISH	: Inner tube - Black Outer cover - Black Finish - Smooth/Wrapped - upto 1" Wrapped from 1.1/4" to 2"
APPLICABLE STD	: Elastohose Proprietary Product

PART NO.	INTERNAL DIAMETER		OUTER DIAMETER	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS		WEIGHT	STD. LENGTH
	Inch	mm		bar	psi	bar	psi	Inch	mm		
EHAW137-06	1/4	6	13	20	300	60	900	1.9	48	0.170	100/50
EHAW137-08	5/16	8	15	20	300	60	900	2.5	64	0.220	100/50
EHAW137-10	3/8	10	17	20	300	60	900	3.1	80	0.260	100/50
EHAW137-12	1/2	12.5	21	20	300	60	900	4.1	104	0.350	100/50
EHAW137-16	5/8	16	24	20	300	60	900	5.1	130	0.440	100/50
EHAW137-19	3/4	19	27	20	300	60	900	6.0	152	0.530	100/50
EHAW137-25	1	25	35	20	300	60	900	7.9	200	0.750	100/50
EHAW137-32	1.1/4	32.5	43	20	300	60	900	9.8	250	1.200	60/40
EHAW137-38	1.1/2	38	50	20	300	60	900	11.8	300	1.450	60/40
EHAW137-51	2	51	64	20	300	60	900	16.5	420	1.800	40