

ARGON GAS WELDING HOSE



TUBE	: Natural and Synthetic rubber blend
REINFORCEMENT	: High Tenacity Synthetic Textile braid
COVER	: Natural and Synthetic rubber blend resistant to Ozone, abrasion and heat
TEMP RANGE	: -25°C + 80°C (-13°F +176°F)
APPLICATIONS	: For Welding / Cutting Purpose
PROPERTIES	: Ozone resistance Heat Resistance Flexible Uniform Thickness
STANDARD COLOUR AND FINISH	: Inner tube - Black Outer cover - Black Finish - Smooth
APPLICABLE STD	: EN ISO 3821, IS 447

PART NO.	INNER DIAMETER		OUTER DIAMETER	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS		WEIGHT	STD. LENGTH
	Inch	mm		bar	psi	bar	psi	Inch	mm		
EHAR152-06	1/4	6	13	20	300	60	900	1.9	48	0.160	50 / 100
EHAR152-08	5/16	8	15	20	300	60	900	2.5	64	0.220	50 / 100
EHAR152-10	3/8	10	17	20	300	60	900	3.9	100	0.250	50 / 100

Note : Available in 6 ft, 10 ft, 25 ft, 50 ft and 100 ft length with 5/8 UNF - 18 RH fittings